



# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Date of issue: 11/22/2022 Version: 1.0

### SECTION 1: Identification 1.1. Identification

Product form : Mixture  
Product name : ProPoxy Ice Blue  
Product code : 1322306

### 1.2. Recommended use and restrictions on use

Recommended use : Industrial use  
Restrictions on use : The product is intended for professional use

### 1.3. Supplier

Modern Recreational Technologies, Inc.  
2220 Highway 70 SE, Suite 100  
Hickory, NC 28602  
United States  
1-800-728-8258

### 1.4. Emergency telephone number

Emergency number: Chemtel (USA & Canada): 800-424-9300  
Chemtel (International): 703-527-3887

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS US classification

Flammable liquids Category 3	H317 May cause an allergic skin reaction
Skin sensitization, Category 1	H340 May cause genetic defects
Germ cell mutagenicity Category 1B Carcinogenicity Category 1B	H350 May cause cancer
Specific target organ toxicity (repeated exposure) Category 2 H226 Flammable liquid and vapor	H373 May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling



Hazard pictograms (GHS US) :  
Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H317 - May cause an allergic skin reaction  
H315 - Causes skin irritation and eye irritation  
H340 - May cause genetic defects  
H350 - May cause cancer  
H351 - May damage fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 - Contaminated work clothing must not be allowed out of the workplace.

11/22/2022 EN (English US) Page 1

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Titanium Dioxide	(CAS-No.) 13463-67-7	33.273 – 36.97	Carc. 2, H351
METHYL NORMAL AMYL KETONE - 6.74	(CAS-No.) 110-43-0	10.28 – 12.336	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
ETHYL ACETATE	(CAS-No.) 141-78-6	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethylbenzene	(CAS-No.) 100-41-4	0.462 – 1.081	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7	0.35 – 0.467	Flam. Liq. 4, H227 Skin Sens. 1, H317
METHYL-ISOBUTYL KETONE - 6.67	(CAS-No.) 108-10-1	0.462 – 0.467	Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
AROMATIC 100 - 7.29	(CAS-No.) 64742-95-6	0.326 – 0.34	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Diisobutyl ketone	CAS-No.) 108-83-8	1-5	Flam. Liq 3, H226 Acute Tox. 3(Inhalation), H335 Acute Haz. 3(Aquatic), H402

Xylene	CAS-No.) 108-83-8	1-5	Flam. Liq. 3, H226 Acute Tox. 5 (Oral) H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Carc. 2, H351
Carbon Black	CAS-No.) 108-83-8	1-7	Skin Irrit. 2 H315

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

11/22/2022 EN (English US) 2/9

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>AROMATIC 100 - 7.29 (64742-95-6)</b>		
Not applicable		
<b>ethylbenzene (100-41-4)</b>		
ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH TWA (ppm)	20 ppm

11/22/2022 EN (English US) 3/9

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ethylbenzene (100-41-4)</b>		
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Titanium Dioxide (13463-67-7)</b>		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019

OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>ETHYL ACETATE (141-78-6)</b>		
ACGIH	Local name	Ethyl acetate
ACGIH	ACGIH TWA (ppm)	400 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>		
Not applicable		
<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>		
ACGIH	Local name	Methyl isobutyl ketone
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; dizziness; headache. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)</b>		
ACGIH	Local name	Methyl n-amyl ketone
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & skin irr
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	465 mg/m <sup>3</sup>

OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>XYLENE(108-83-8)</b>		
ACGIH TLV	Local Name	Xylene
ACIGH	ACIGH TWA (ppm)	100 ppm
ACIGH	Remark(ACGIH)	TLV Basis: Eye & skin irr Notations: A3 (Confirmed Animal carcinogen)
ACIFH	Regulatory reference	ACIGH 2019
OSHA	OSHA PEL (TWA)(ppm)	100 ppm
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
OSHA	Regulatory reference(US-OSHA)	OSHA Annotated Table Z-1
<b>DIBK(108-83-8)</b>		
ACGIH TLV	Local Name	Diisobutyl Ketone
ACIGH	ACIGH TWA (ppm)	25 ppm
ACIGH	Remark(ACGIH)	TLV Basis: URT & eye irrr
ACIFH	Regulatory reference	ACIGH 2021
OSHA	OSHA PEL (TWA)(mg/m <sup>3</sup> )	50 ppm
OSHA	OSHA PEL (TWA) (ppm)	290 mg/m <sup>3</sup>
OSHA	Regulatory reference(US-OSHA)	OSHA Annotated Table Z-1

<b>Carbon Black(1333-86-4)</b>		
<b>ACGIH TLV</b>	Local Name	Carbon Black
<b>ACIGH</b>	ACIGH TWA (ppm)	3 ppm
<b>ACIGH</b>	Remark(ACGIH)	TLV Basis: Inhalable fracton
<b>ACIGH</b>	Regulatory reference	ACIGH 2019
<b>OSHA</b>	OSHA PEL (TWA)(mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
<b>OSHA</b>	Regulatory reference(US-OSHA)	OSHA Annotated Table Z-1

11/22/2022 EN (English US) 4/9

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

Color : Blue

Odor : characteristic

Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 80 °F Based on data available for ingredients Relative evaporation rate (butyl acetate=1) : No data available  
Flammability (solid, gas) : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Density : 11.63 lb/gal  
Solubility : No data available  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosion limits : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available

## 9.2. Other information

No additional information available

11/22/2022 EN (English US) 5/9

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))



ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>Titanium Dioxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
<b>ETHYL ACETATE (141-78-6)</b>	
LD50 oral rat	10200 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	> 20000 mg/kg body weight (24 hour cuff method, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	10200 mg/kg body weight
<b>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
LD50 oral rat	> 2000 mg/kg (Rat, Literature study, Oral)
<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>	
LD50 oral rat	2080 mg/kg (Equivalent or similar to OECD 401, Rat, Experimental value, Oral)
LD50 dermal rat	≥ 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	8.2 – 16.4 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (vapours))
ATE US (oral)	2080 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	8.2 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)</b>	
LD50 oral rat	1600 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
<b>2,6-Dimethyl-4-heptanone (108-83-8)</b>	
LD50 oral rat	5750 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)

LC50 Inhalation - Rat	> 14.5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (vapours), 14 day(s))
<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3608mg/kg
LSD50 dermal rabbit	14100 mg/kg
LC50 Inhalation - Rat	4330 ppm 6 h
<b>Carbon Black(1333-86-4)</b>	
LD50 oral rat	>8,000 mg/kg

11/22/2022 EN (English US) 6/9

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)</b>	
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1600 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Titanium Dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>	
---	--

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified  
 STOT-single exposure : Not classified

<b>ETHYL ACETATE (141-78-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

<b>ethylbenzene (100-41-4)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>xylene (1330-20-7)</b>	
STOT single exposure	Respiratory system Central nervous system 2B - Possibly carcinogenic to humans

<b>DIBK (100-41-4)</b>	
STOT-single exposure	May cause respiratory irritation

<b>Carbon Black (1333-86-4)</b>	
STOT-repeated exposure	May cause respiratory irritation

Aspiration hazard : Not classified  
 Viscosity, kinematic : No data available  
 Symptoms/effects after skin contact : May cause an allergic skin reaction.

## SECTION 12: Ecological information

No ecotoxicological studies have been conducted on this product by Sumter Coatings.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Additional information :  
 Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

11/22/2022 EN (English US) 7/9

# 1322306

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 3 - Flammable liquid



### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

<b>AROMATIC 100 - 7.29 (64742-95-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>ethylbenzene (100-41-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
<b>Titanium Dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>ETHYL ACETATE (141-78-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb
<b>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb
<b>METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Xylene (1330-20-7)</b>	

Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>DIBK (108-10-1)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Carbon Black (1333-86-4)</b>
Subject to reporting requirements of United States SARA Section 313

## 15.2. International regulations

### CANADA

<b>AROMATIC 100 - 7.29 (64742-95-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>ethylbenzene (100-41-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Titanium Dioxide (13463-67-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>ETHYL ACETATE (141-78-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>DIBK (108-10-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Xylene (1330-20-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

### EU-Regulations

No additional information available

### National regulations

<b>ethylbenzene (100-41-4)</b>
Listed on IARC (International Agency for Research on Cancer)
<b>Titanium Dioxide (13463-67-7)</b>
Listed on IARC (International Agency for Research on Cancer)

<b>METHYL-ISOBUTYL KETONE - 6.67 (108-10-1)</b>
Listed on IARC (International Agency for Research on Cancer)
<b>Xylene (1330-20-7)</b>
Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

**WARNING:** This product can expose you to METHYL-ISOBUTYL KETONE - 6.67, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer

H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*