

# SAFETY DATA SHEET

# PETTIT



Revision Date 18-Nov-2015  
Version 2

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** Pettit Ultima SR-60 Antifouling Paint 1038 Black  
**Product code** 1103900

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Paint  
**Restrictions on use** Read label instructions and SDS

### 1.3 Details of the supplier of the safety data sheet

**Supplier** Kop-Coat, Inc.  
Marine Group  
36 Pine Street  
Rockaway, NJ 07866  
1-800-221-4466

### 1.4 Emergency telephone number

**Emergency telephone number** Chemtrec: +1 703-527-3887 ex-USA  
Chemtrec: 1-800-424-9300 USA

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Flammable liquids	Category 3

### 2.2 Label elements

#### Signal Word

Danger

**Hazard Statements**

Harmful if swallowed  
 Causes serious eye damage  
 May cause an allergic skin reaction  
 May cause cancer  
 Flammable liquid and vapor



**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing must not be allowed out of the workplace  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
 IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**2.3. Other Hazards Hazards not otherwise classified (HNOC)**

Not Applicable

**2.4 Other information**

Not Applicable

**Unknown Acute Toxicity** 1.56800035% of the mixture consists of ingredient(s) of unknown toxicity

### 3. Composition/Information on Ingredients

**Substance**

**Mixture**

Chemical Name	CAS-No	Weight %
Cuprous oxide	1317-39-1	60 - 70
n-Propanol	71-23-8	10 - 20
Resin acids	Proprietary	5 - 10
Zinc oxide	1314-13-2	1 - 5
Xylene	1330-20-7	1 - 5
Cupric Oxide	1317-38-0	1 - 5
Carbon black	1333-86-4	1 - 5
Copper (as Cu Dust & Mists)	7440-50-8	1 - 5
HEAVY AROMATIC NAPHTHA	64742-94-5	< 1
Ethylbenzene	100-41-4	< 1
SILICA (CRYSTALLINE-CRISTOBALITE)	14464-46-1	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### 4.1 Description of first-aid measures

<b>General advice</b>	For further assistance, contact your local Poison Control Center.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.
<b>Skin contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice.
<b>Inhalation</b>	Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice.
<b>Ingestion</b>	Rinse mouth. Do NOT induce vomiting. Call a physician or poison control center immediately. If a person vomits when lying on his back, place him in the recovery position.

### 4.2 Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	See Section 2.2, Label Elements and/or Section 11, Toxicological effects.
-----------------	---

### 4.3 Indication of any immediate medical attention and special treatment needed

<b>Notes to physician</b>	There is no specific antidote for effects from overexposure to this material. Treat symptomatically.
---------------------------	--

## 5. Fire-Fighting Measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

### 5.2 Special hazards arising from the substance or mixture

#### Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

**Hazardous Combustion Products** Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

**Explosion Data**

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** Yes.

**5.3 Advice for firefighters**

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

## 6. Accidental Release Measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

**6.2 Environmental precautions**

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

**6.3 Methods and materials for containment and cleaning up**

**Methods for Containment**

Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges.

## 7. Handling and storage

**7.1 Precautions for safe handling**

**Advice on safe handling**

Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.

**Hygiene measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.

**Materials to Avoid** No materials to be especially mentioned.

## 8. Exposure controls/personal protection

### 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Cuprous oxide 1317-39-1	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-				
n-Propanol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m <sup>3</sup>	TWA: 100 ppm	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 250 ppm STEL: 614 mg/m <sup>3</sup> Skin	TWA: 100 ppm
Zinc oxide 1314-13-2	STEL: 10 mg/m <sup>3</sup> respirable fraction TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm
Cupric Oxide 1317-38-0	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-				
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
Copper (as Cu Dust & Mists) 7440-50-8	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm
SILICA (CRYSTALLINE-CRIS TOBALITE) 14464-46-1	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	: (1/2)(30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (1/2)(250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (1/2)(10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>

### 8.2 Appropriate engineering controls

#### Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### 8.3 Individual protection measures, such as personal protective equipment

#### Eye/Face Protection

Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles. Face-shield.

#### Skin and body protection

Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use. Long sleeved clothing. Protective shoes or boots.

#### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**

See section 7 for more information

**9. Physical and chemical properties****9.1 Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Appearance</b>	No information available
<b>Color</b>	Black
<b>Odor</b>	Hydrocarbon-like
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
<b>pH</b>		No information available
<b>Melting/freezing point</b>		No information available
<b>Boiling point/boiling range</b>		No information available
<b>Flash Point</b>	23.3 °C / 74 °F	
<b>Evaporation rate</b>		No information available
<b>Flammability (solid, gas)</b>		No information available
<b>Flammability Limits in Air</b>		
upper flammability limit		No information available
lower flammability limit		No information available
<b>Vapor pressure</b>		No information available
<b>Vapor density</b>		No information available
<b>Specific Gravity</b>		No information available
<b>Water solubility</b>		No information available
<b>Solubility in other solvents</b>		No information available
<b>Partition coefficient</b>		No information available
<b>Autoignition temperature</b>		No information available
<b>Decomposition temperature</b>		No information available
<b>Viscosity, kinematic</b>	> 22 mm <sup>2</sup> /s	
<b>Viscosity, dynamic</b>		No information available
<b>Explosive properties</b>		No information available
<b>Oxidizing Properties</b>		No information available

**9.2 Other information**

<b>Volatile organic compounds (VOC) content</b>	374 g/L
<b>Density</b>	20.23 lb/gal

**10. Stability and Reactivity****10.1 Reactivity**

No dangerous reaction known under conditions of normal use

**10.2 Chemical stability**

Stable under recommended storage conditions

**10.3 Possibility of hazardous reactions**

None under normal processing.

**10.4 Conditions to Avoid**

Keep away from heat, sparks and flames.

**10.5 Incompatible Materials**

No materials to be especially mentioned.

**10.6 Hazardous Decomposition Products**

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

**11. Toxicological information****11.1 Acute toxicity****Numerical measures of toxicity: Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**Unknown Acute Toxicity** 1.56800035% of the mixture consists of ingredient(s) of unknown toxicity

<b>Oral LD50</b>	709.00 mg/kg
<b>LC50 (Dust/Mist)</b>	161.90 mg/l
<b>LC50 (Vapor)</b>	452.00 mg/l

**Numerical measures of toxicity: Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Cuprous oxide 1317-39-1	470 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	= 5 mg/L ( Rat ) 4 h
n-Propanol 71-23-8	3830 mg/kg ( Rat )	> 10000 mg/kg ( Rabbit )	> 13548 ppm ( Rat ) 4 h
Zinc oxide 1314-13-2	5000 mg/kg ( Rat )	-	-
Xylene 1330-20-7	3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
HEAVY AROMATIC NAPHTHA 64742-94-5	5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
Ethylbenzene 100-41-4	3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**11.2 Information on toxicological effects****Skin corrosion/irritation**Product Information

- No information available

Component Information

- No information available

**Eye damage/irritation**Product Information

- No information available

Component Information

- No information available

**Respiratory or skin sensitization**Product Information

- No information available

Component Information

- No information available

**Germ cell mutagenicity**Product Information

- No information available

Component Information

- No information available

**Carcinogenicity**Product Information

- The table below indicates whether each agency has listed any ingredient as a carcinogen

Component Information

- Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon black 1333-86-4	-	Group 2B	-	
Ethylbenzene 100-41-4	-	Group 2B	-	
SILICA (CRYSTALLINE-CRISTOBA LITE) 14464-46-1	A2	Group 1	-	

**Reproductive toxicity**Product Information

- No information available

Component Information

- No information available

**STOT - single exposure**

No information available

**STOT - repeated exposure**

- No information available

**Other adverse effects**Product Information

- No information available

Component Information

- No information available

**Aspiration hazard**Product Information

- No information available

Component Information

- No information available

## 12. Ecological information

**12.1 Toxicity****Ecotoxicity**

No information available

3.91912 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Cuprous oxide 1317-39-1	EC50: 96 h <i>Desmodesmus subspicatus</i> 65 mg/L EC50: 96 h <i>Pseudokirchneriella subcapitata</i> 0.021 - 0.037 mg/L EC50: 96 h <i>Pseudokirchneriella subcapitata</i> 0.055 - 0.076 mg/L static	-	EC50: 48 h <i>Daphnia magna</i> 0.51 mg/L
n-Propanol 71-23-8	-	LC50: 96 h <i>Pimephales promelas</i> 4480 mg/L flow-through	EC50: 48 h <i>Daphnia magna</i> 3642 mg/L EC50: 48 h <i>Daphnia magna</i> 3339 - 3977 mg/L Static
Xylene 1330-20-7	-	LC50: 96 h <i>Pimephales promelas</i> 23.53 - 29.97 mg/L static LC50: 96 h <i>Cyprinus carpio</i> 780 mg/L semi-static LC50: 96 h <i>Cyprinus</i>	EC50: 48 h water flea 3.82 mg/L LC50: 48 h <i>Gammarus lacustris</i> 0.6 mg/L



		carpio 780 mg/L LC50: 96 h Poecilia reticulata 30.26 - 40.75 mg/L static LC50: 96 h Pimephales promelas 13.4 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L static LC50: 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L LC50: 96 h Lepomis macrochirus 13.1 - 16.5 mg/L flow-through LC50: 96 h Lepomis macrochirus 19 mg/L LC50: 96 h Lepomis macrochirus 7.711 - 9.591 mg/L static	
Copper (as Cu Dust & Mists) 7440-50-8	EC50: 72 h Pseudokirchneriella subcapitata 0.0426 - 0.0535 mg/L static EC50: 96 h Pseudokirchneriella subcapitata 0.031 - 0.054 mg/L static	LC50: 96 h Pimephales promelas 0.0068 - 0.0156 mg/L LC50: 96 h Pimephales promelas 0.3 mg/L static LC50: 96 h Pimephales promelas 0.2 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 0.052 mg/L flow-through LC50: 96 h Lepomis macrochirus 1.25 mg/L static LC50: 96 h Cyprinus carpio 0.3 mg/L semi-static LC50: 96 h Cyprinus carpio 0.8 mg/L static LC50: 96 h Poecilia reticulata 0.112 mg/L flow-through	EC50: 48 h Daphnia magna 0.03 mg/L Static
HEAVY AROMATIC NAPHTHA 64742-94-5	-	LC50: 96 h Pimephales promelas 19 mg/L static LC50: 96 h Oncorhynchus mykiss 2.34 mg/L LC50: 96 h Lepomis macrochirus 1740 mg/L static LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Pimephales promelas 41 mg/L	EC50: 48 h Daphnia magna 0.95 mg/L
Ethylbenzene 100-41-4	EC50: 72 h Pseudokirchneriella subcapitata 4.6 mg/L EC50: 96 h Pseudokirchneriella subcapitata 438 mg/L EC50: 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L static EC50: 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L static	LC50: 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L static LC50: 96 h Oncorhynchus mykiss 4.2 mg/L semi-static LC50: 96 h Pimephales promelas 7.55 - 11 mg/L flow-through LC50: 96 h Lepomis macrochirus 32 mg/L static LC50: 96 h Pimephales promelas 9.1 - 15.6 mg/L static LC50: 96 h Poecilia reticulata 9.6 mg/L static	EC50: 48 h Daphnia magna 1.8 - 2.4 mg/L

## 12.2 Persistence and degradability

No information available.

## 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
n-Propanol 71-23-8	0.34
Xylene 1330-20-7	3.15
HEAVY AROMATIC NAPHTHA 64742-94-5	6.1
Ethylbenzene 100-41-4	3.118

## 12.4 Mobility in soil

No information available.

## 12.5 Other adverse effects

No information available

### 13. Disposal Considerations

#### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

### 14. Transport Information

<b>Note</b>	Limited quantity This product may be reclassified as Consumer Commodity, ORM-D, when shipped by ground; packaging quantity limitations apply.
<b>DOT</b>	Quarts and gallons ship as limited quantity.
<b>MEX</b>	no data available
<b>IMDG</b>	
<b>Proper shipping name</b>	UN1263, Paint, 3, III
<b>IATA</b>	
<b>Proper shipping name</b>	UN1263, Paint, 3, III

### 15. Regulatory information

#### 15.1 International Inventories

<b>TSCA</b>	Complies
<b>DSL</b>	Complies
<b>EINECS/ELINCS</b>	-
<b>ENCS</b>	-
<b>IECSC</b>	-
<b>KECL</b>	-
<b>PICCS</b>	-
<b>AICS</b>	-
<b>NZIoC</b>	-

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

#### 15.2 U.S. Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Cuprous oxide 1317-39-1	1.0
Zinc oxide 1314-13-2	1.0
Xylene 1330-20-7	1.0
Cupric Oxide	1.0

1317-38-0	
Copper (as Cu Dust & Mists) 7440-50-8	1.0
Ethylbenzene 100-41-4	0.1

### 15.3 Pesticide Information

#### U.S. EPA Pesticide Information

EPA Pesticide Registration Number 60061-49

#### EPA Statement

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

#### EPA Pesticide Label

WARNING. May be fatal if swallowed or inhaled. Causes moderate eye irritation. Harmful if absorbed through skin.

### 15.4 U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Carbon black - 1333-86-4	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
CUMENE - 98-82-8	Carcinogen
Crystalline silica (Quartz) (Respirable) - 14808-60-7	Carcinogen
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
NAPHTHALENE - 91-20-3	Carcinogen
Cadmium - 7440-43-9	Carcinogen Developmental Male Reproductive
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

### 16. Other information

<b>NFPA</b>	<b>Health Hazard 2</b>	<b>Flammability 2</b>	<b>Instability 0</b>	<b>Physical and chemical hazards -</b>
<b>HMIS</b>	<b>Health Hazard 2*</b>	<b>Flammability 2</b>	<b>Physical Hazard 0</b>	<b>Personal protection X</b>

#### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S\*)

STEL (Short Term Exposure Limit)

---

*TLV® (Threshold Limit Value)*

*TWA (time-weighted average)*

**Revision Date** 18-Nov-2015

**Revision Note**

No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**