



## ANTIFOULING COMPATIBILITY CHART

	Hard Antifouling	Durable Ablative	Soft Ablative	Modified Antifouling	Freshwater Antifouling
<div style="border: 1px solid black; padding: 5px; width: fit-content; margin-bottom: 10px;">Existing Bottom Paint</div> <div style="border: 1px solid black; padding: 5px; width: fit-content;">New Bottom Paint</div>	Baltoplate Black Widow Bottomkote Aqua Bottom Pro Gold! BottomShield Defense Vivid Epoxy Cop Sharkskin Talon Trinidad (All) Tropikote Ultra Ultra-Kote Unepoxy (All) VC Offshore	Cukote Hydrocoat (All) Horizons Micron CSC Micron Extra Micron Optima Neptune 5 PCA Gold! Trilux 33 Ultima SR-40 Ultima SR-60	Ablative Plus AF-33 ACT Aqua-One Bottomkote NT CPP Micron CF Micron Optima Micron WA Monterey Pacifica Plus Proguard Ablative Smart Solution Super B Ablative Ultima Eco Armor	Biocop TF* Bottomkote Pro Micron 99* Micron 66* Seamate Ultima SSA Islands 44 TF* Tropikote EX* Islands 44 Plus* Biotin Plus*	FW 21 VC 17 SR 21 VMG
<b>Black Widow™</b> <b>Trinidad™ SR</b> <b>Trinidad™ Pro</b> <b>Trinidad™ HD</b> <b>Vivid™</b>	Sand and Apply	Heavy Sand and Apply	Remove	Remove	Remove
<b>ECO HRT™</b> <b>Premium HRT™</b> <b>Unepoxy HRT™</b>	Sand and Apply	Light Sand and Apply	Light Sand and Apply	Sand and Apply	Remove
<b>Odyssey™ HD</b> <b>Ultima SR-40™</b> <b>Ultima SR-60™</b> <b>Barracuda™</b>	Sand and Apply	Light Sand and Apply	Sand and Apply	Heavy Sand and Apply	Remove
<b>Hydrocoat™</b> <b>Hydrocoat SR™</b> <b>Hydrocoat Eco™</b> <b>Neptune HRT™</b>	Light Sand and Apply	Powerwash and Apply	Light Sand and Apply	Sand and Apply	Sand and Apply
<b>SR 21™</b>	Sand and Apply	Remove	Remove	Remove	Clean and Apply

Bottomkote NT™, Aqua™, ACT™, Micron CSC™, Micron Optima™, Micron Extra™, Micron WA™, Proguard Ablative™, Micron 99™, Micron 66™, VC-17™, Baltoplate™, Epoxy Cop™, Ultra™, VC Offshore™ and Pacifica Plus™ refer to products sold by Interlux®. Armor™ refers to a product sold by Flexdel. Sharkskin™, Talon™, Tropikote™, Cukote™, Biocop TF™, Islands 44 TF™, Tropikote EX™, Islands 44 Plus™, Biotin Plus™, Monterey™, Smart Solution™, VMG and AF33™ refer to products sold by New Nautical Coatings.

\*Tin copolymer paints and certain additional modified antifouling paints should be sealed with a coat of 6627 Tie Coat Primer, allow to dry 4 hours and apply new antifouling paint. This document is intended as a guide only, additional preparation may be involved due to condition and age of substrate.