

ANTIFOULING COMPATIBILITY CHART

| EXISTING BOTTOM PAINT | | | | |
|--|---|---|---|--------------------------------|
| HARD ANTIFOULING | DURABLE ABLATIVE | SOFT ABLATIVE | MODIFIED ANTIFOULING | FRESHWATER ANTIFOULING |
| Baltoplate Black Widow Bottomkote Aqua Bottom Pro Gold! Bottom Shield Defense Vivid Epoxy Cop Sharkskin Talon Trinidad (All) Tropikote Ultra Ultra-Kote Unepoxy (All) VC Offshore | Cukote Hydrocoat (All) Horizons Micron CSC Micron Extra Micron Optima Neptune 5 PCA Gold! Trilux 33 Ultima SR-40 Ultima SR-60 | Ablative Plus AF-33 ACT Aqua-One Bottomkote NT CPP Micron CF Micron Optima Micron WA Monterey Pacifica Plus Proguard Ablative Smart Solution Super B Ablative Ultima Eco Armor | Biocop TF* Bottomkote Pro Micron 99* Micron 66* Seamate Ultima SSA Islands 44 TF* Tropikote EX* Islands 44 Plus* Biotin Plus * | FW 21 VC 17 SR 21 VMG |

| NEW BOTTOM PAINT | Black Widow™ Trinidad™ SR Trinidad™ Pro Trinidad™ HD Vivid™ | Sand and Apply | Remove | Remove | Remove | Remove |
|------------------|---|----------------------|----------------------|----------------------|----------------------|-----------------|
| | ECO HRT™ Premium HRT™ Unepoxy HRT™ | Sand and Apply | Light Sand and Apply | Light Sand and Apply | Sand and Apply | Remove |
| | Odyssey™ HD Ultima SR-40™ Ultima SR-60™ Barracuda™ | Sand and Apply | Light Sand and Apply | Sand and Apply | Heavy Sand and Apply | Remove |
| | Hydrocoat™ Hydrocoat SR™ Hydrocoat Eco™ Neptune HRT™ | Light Sand and Apply | Power wash and Apply | Light Sand and Apply | Sand and Apply | Sand and Apply |
| | SR 21™ | Sand and Apply | Remove | Remove | Remove | Clean and Apply |

Bottomkote NT™, Aqua™, ACT™, Micron CSC™, Micron Optima™, Micron Extra™, Micron WA™, Proguard Ablative™, Micron 99™, Micron 66™, VC-17™, Baltoplate™, Epoxy Cop™, Ultra™, VC Offshore™ and Pacifica Plus™ refer to products sold by Interlux®. Armor™ refers to a product sold by Flexdel. Sharkskin™, Talon™, Tropikote™, Cukote™, Biocop TF™, Islands 44 TF™, Tropikote EX™, Islands 44 Plus™, Biotin Plus™, Monterey™, Smart Solution™, VMG and AF33™ refer to products sold by New Nautical Coatings.

*Tin copolymer paints and certain additional modified antifouling paints should be sealed with a coat of 6627 Tie Coat Primer, allow to dry 4 hours and apply new antifouling paint. This document is intended as a guide only, additional preparation may be involved due to condition and age of substrate.