# **SAFETY DATA SHEET**



Revision Date 10-Mar-2016

Version 1

# 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** Z\*SPAR V-975 Captain's Satin Sheen Varnish

Product code 8797500

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Paint/Paint Related Material Restrictions on use Paint/Paint Related Material Read label instructions and SDS

### 1.3 Details of the supplier of the safety data sheet

Supplier Kop-Coat, Inc. / Pettit Marine Paint

Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

### 1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA

Chemtrec: 1-800-424-9300 USA

### 2. Hazards identification

# 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910.1200

Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

### 2.2 Label elements

# Signal Word

Danger

#### **Hazard Statements**

May cause an allergic skin reaction Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure Flammable liquid and vapor



### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Contaminated work clothing should not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention
If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

In case of fire: Use CO2, dry chemical, or foam to extinguish

# **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

### 2.4 Other information

Not Applicable

**Unknown Acute Toxicity** 

1.02231% of the mixture consists of ingredient(s) of unknown toxicity

# 3. Composition/Information on Ingredients

Substance
Not applicable
Mixture

Chemical Name	CAS-No	Weight %
Stoddard Solvent	8052-41-3	40 - 50

Distillates, petroleum, hydrotreated light	64742-47-8	5 - 10
Amorphous Silica	7631-86-9	1 - 5
Methyl ethyl ketoxime	96-29-7	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First aid measures

## 4.1 Description of first-aid measures

General advice For further assistance, contact your local Poison Control Center.

**Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.

**Skin contact** Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated

clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center

or doctor for treatment advice.

**Inhalation** Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Call a poison control center or doctor for treatment advice.

Ingestion Rinse mouth. Do NOT induce vomiting. If a person vomits when lying on his back, place

him in the recovery position. Call a physician or poison control center immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician There is no specific antidote for effects from overexposure to this material. Treat

symptomatically.

# 5. Fire-Fighting Measures

## 5.1 Extinguishing media

## Suitable extinguishing media

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media Water may be unsuitable for extinguishing fires.

### 5.2 Special hazards arising from the substance or mixture

#### Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion of absorbent material contaminated with this product Air oxidation of certain components of this product may cause waste soaked with this product to spontaneously combust.

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

#### **Explosion Data**

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Yes.

#### 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool

containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

### 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

#### 6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

### 6.3 Methods and materials for containment and cleaning up

Methods for Containment Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal. Prevent further

leakage or spillage if safe to do so.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use non-sparking tools

and equipment.

## 7. Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking. There is a hazard associated with rags, paper or any other material used to remove spills which become soaked with product. Avoid accumulation of these: they are to be disposed off safely after use. Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion of absorbent material contaminated with this product.

Hygiene measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

# 7.2 Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.

Materials to Avoid

No materials to be especially mentioned.

### 8. Exposure controls/personal protection

#### 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Stoddard Solvent	TWA: 100 ppm	TWA: 500 ppm	TWA: 290 mg/m <sup>3</sup>	TWA: 100 ppm	TWA: 100 ppm	TWA: 525 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	STEL: 580 mg/m <sup>3</sup>	TWA: 572 mg/m <sup>3</sup>	TWA: 525 mg/m <sup>3</sup>	
Distillates, petroleum, hydrotreated light 64742-47-8	-	-	TWA: 200 mg/m <sup>3</sup> Skin			
Amorphous Silica 7631-86-9	-	TWA: 20 mppcf : (80)/(% SiO2) mg/m³ TWA				

### 8.2 Appropriate engineering controls

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable

this should be achieved by the use of local exhaust ventilation and good general extraction. Use adequate ventilation to maintain airborne concentrations at levels below permissible or

recommended occupational exposure limits.

8.3 Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Wear suitable protective clothing. Remove and wash contaminated clothing before re-use.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

**Hygiene measures** See section 7 for more information

# 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid

Appearance Semi-transparent

**Color** Amber

Odor Hydrocarbon-like
Odor Threshold No information available

Property Values Remarks • Methods

pH No information available
Melting/freezing point No information available

Boiling point/boiling range

No information available

Flash Point 39 °C / 102 °F

Evaporation rate

No information available

Flammability (solid, gas)

No information available Flammability Limits in Air

upper flammability limitNo information availablelower flammability limitNo information availableVapor pressureNo information available

Vapor density

No information available

Specific Gravity 0.905

Water solubility 0.905

No information

Water solubilityNo information availableSolubility in other solventsNo information availablePartition coefficientNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information available

Viscosity, kinematic > 22 mm2/s

Viscosity, dynamic No information available

Explosive properties No information available Oxidizing Properties No information available

9.2 Other information

Volatile organic compounds (VOC) 483 g/L

content

**Density** 7.54 lb/gal

# 10. Stability and Reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use

### 10.2 Chemical stability

Stable under recommended storage conditions

### 10.3 Possibility of hazardous reactions

None under normal processing.

#### 10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

### 10.5 Incompatible Materials

No materials to be especially mentioned.

### 10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

10-Mar-2016 - 8797500 - 1 - AGHS - English -

# 11. Toxicological information

### 11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**Unknown Acute Toxicity** 1.02231% of the mixture consists of ingredient(s) of unknown toxicity

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates, petroleum, hydrotreated light 64742-47-8	5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
Amorphous Silica 7631-86-9	5000 mg/kg ( Rat )	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h
Methyl ethyl ketoxime 96-29-7	930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h

### 11.2 Information on toxicological effects

### Skin corrosion/irritation

**Product Information** 

- No information available
- **Component Information**
- · No information available

### Eye damage/irritation

Product Information

- No information available
- Component Information
- · No information available

#### Respiratory or skin sensitization

**Product Information** 

- No information available
- Component Information
- · No information available

### Germ cell mutagenicity

Product Information

- No information available
- Component Information
- No information available

### Carcinogenicity

Product Information

• No information available

**Component Information** 

· Contains a known or suspected carcinogen

# Reproductive toxicity

Product Information

· No information available

Component Information

No information available

10-Mar-2016 - 8797500 - 1 - AGHS - English -

\_\_\_\_\_

### STOT - single exposure

No information available

### STOT - repeated exposure

No information available

#### Other adverse effects

Product Information

No information available

Component Information

• No information available

### **Aspiration hazard**

Product Information

• No information available

**Component Information** 

· No information available

# 12. Ecological information

### 12.1 Toxicity

**Ecotoxicity** 

No information available

< 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects** 

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Distillates, petroleum, hydrotreated light 64742-47-8	-	LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Lepomis macrochirus 2.2 mg/L static LC50: 96 h Oncorhynchus mykiss 2.4 mg/L static	-
Amorphous Silica 7631-86-9	EC50: 72 h Pseudokirchneriella subcapitata 440 mg/L	LC50: 96 h Brachydanio rerio 5000 mg/L static	EC50: 48 h Ceriodaphnia dubia 7600 mg/L
Methyl ethyl ketoxime 96-29-7	EC50: 72 h Desmodesmus subspicatus 83 mg/L	LC50: 96 h Pimephales promelas 777 - 914 mg/L flow-through LC50: 96 h Poecilia reticulata 760 mg/L static	EC50: 48 h Daphnia magna 750 mg/L

### 12.2 Persistence and degradability

No information available.

#### 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Methyl ethyl ketoxime	0.65
96-29-7	

### 12.4 Mobility in soil

No information available.

### 12.5 Other adverse effects

No information available

# 13. Disposal Considerations

#### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations. Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion of absorbent material contaminated with this product.

# 14. Transport Information

Note DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)"

**DOT** Not regulated (If shipped in NON BULK packaging by ground transport)

MEX no data available

**IMDG** 

Proper shipping name UN1263, Paint, 3, III

IATA

Proper shipping name UN1263, Paint, 3, III

# 15. Regulatory information

### 15.1 International Inventories

TSCA Complies DSL Complies

 EINECS/ELINCS

 ENCS

 IECSC

 KECL

 PICCS

 AICS

 NZIOC

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

#### 15.2 U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### 15.3 Pesticide Information

Not applicable

### 15.4 U.S. State Regulations

### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65

Crystalline silica (Quartz) (Respirable) - 14808-60-7	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental
	Male Reproductive

# 16. Other information

NFPA Health Hazard 2 Flammability 2 Instability 0 Physical and chemical

hazards HMIS Health Hazard 2\* Flammability 2 Physical Hazard 0 Personal p

Personal protection X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S\*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

Revision Date 10-Mar-2016

**Revision Note** 

No information available

#### Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**