SAFETY DATA SHEET



Revision Date 20-Nov-2017 Version 1

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Product code PROP COAT BARNACLE BARRIER - 1792 1179200

<u>1.2 Relevant identified uses of the substance or mixture and uses advised against</u>

Recommended Use Restrictions on use Paint Read label instructions and SDS

1.3 Details of the supplier of the safety data sheet

Kop-Coat, Inc. / Pettit Marine Paint Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA Chemtrec: 1-800-424-9300 USA

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

2.2 Label elements

Signal Word Warning

Hazard Statements

Causes skin irritation Causes serious eye irritation Suspected of causing cancer May cause damage to organs through prolonged or repeated exposure Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity

< 1% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance Not applicable Mixture

Chemical Name	CAS No.	Weight-%
Xylene	1330-20-7	5 - 10
Heavy aromatic naptha	64742-94-5	1 - 5
ALIPHATIC NAPHTHA	64742-89-8	1 - 5
Zinc oxide	1314-13-2	1 - 5
Ethylbenzene	100-41-4	1 - 5
Naphthalene	91-20-3	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

General advice	For further assistance, contact your local Poison Control Center.			
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.			
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice.			
Inhalation	Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice.			
Ingestion	Rinse mouth. Do NOT induce vomiting. Call a physician or poison control center immediately. If a person vomits when lying on his back, place him in the recovery position.			
4.2 Most important symptoms and effects, both acute and delayed				
Symptoms	See Section 2.2, Label Elements and/or Section 11, Toxicological effects.			
4.3 Indication of any immediate medical attention and special treatment needed				
Notes to physician	There is no specific antidote for effects from overexposure to this material. Treat symptomatically.			
5. Fire-Fighting Measures				

5.1 Extinguishing media

Suitable extinguishing media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media Water may be unsuitable for extinguishing fires.

5.2 Special hazards arising from the substance or mixture

Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

Explosion Data

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Yes.

5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and materials for containment and cleaning up

Methods for Containment	Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use non-sparking tools and equipment.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.				
Hygiene measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.				
7.2 Conditions for safe storage, in	7.2 Conditions for safe storage, including any incompatibilities				
Storage Conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.				
Materials to Avoid	No materials to be especially mentioned.				
8. Exposure controls/personal protection					

8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Xylene	STEL: 150 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	STEL: 150 ppm	TWA: 434 mg/m ³	TWA: 434 mg/m ³	STEL: 150 ppm
		_		STEL: 150 ppm	STEL: 150 ppm	
				STEL: 651 mg/m ³	STEL: 651 mg/m ³	
Zinc oxide	STEL: 10 mg/m ³	TWA: 5 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 10 mg/m ³	TWA: 2 mg/m ³
1314-13-2	respirable fraction	fume	STEL: 10 mg/m ³	STEL: 10 mg/m ³	TWA: 5 mg/m ³	STEL: 10 mg/m ³
	TWA: 2 mg/m ³	TWA: 15 mg/m ³	-	-	STEL: 10 mg/m ³	-
	respirable fraction	total dust			-	
		TWA: 5 mg/m ³				
		respirable fraction				
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	TWA: 20 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 20 ppm
100-41-4		TWA: 435 mg/m ³		TWA: 434 mg/m ³	TWA: 434 mg/m ³	
				STEL: 125 ppm	STEL: 125 ppm	
				STEL: 543 mg/m ³	STEL: 543 mg/m ³	
Naphthalene	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm	TWA: 10 ppm
91-20-3	S*	TWA: 50 mg/m ³	STEL: 15 ppm	TWA: 52 mg/m ³	TWA: 52 mg/m ³	STEL: 15 ppm
			Skin	STEL: 15 ppm	STEL: 15 ppm	Skin
				STEL: 79 mg/m ³	STEL: 79 mg/m ³	
				Skin		

8.2 Appropriate engineering controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles.
Skin and body protection	Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use. Wear suitable protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	See section 7 for more information

9.1 Information on basic physical a Physical state	Liquid		
Appearance	No information available	Color	Gray
Odor	Hydrocarbon-like	Odor Threshold	No information available
Property	Values	Remarks • Methods	
рН		No information available	
Melting/freezing point		No information available	
Boiling point/boiling range Flash Point	138 - 142 °C / 29 °C / 84 °F	XYLENES	
Evaporation rate	29 0 / 84 F	No information available	
Flammability (solid, gas)		No information available	
Flammability Limits in Air			
upper flammability limit		No information available	
lower flammability limit		No information available	
Vapor pressure		No information available	
Vapor density		No information available	
Specific Gravity		No information available	
Water solubility		No information available	
Solubility in other solvents		No information available	
Partition coefficient		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	> 22 mm2/s		
Viscosity, dynamic		No information available	
Explosive properties		No information available	
Oxidizing Properties		No information available	
9.2 Other information			
Volatile organic compounds (VOC) content	487 g/L		
Density	23.42 lb/gal		

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use

10.2 Chemical stability

Stable under recommended storage conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

10.5 Incompatible Materials

No materials to be especially mentioned.

10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity	< 1% of the mixture consists of ingredient(s) of unknown toxicity
Oral LD50 Dermal LD50	24,739.00 mg/kg 11,461.00 mg/kg
LC50 (Dust/Mist)	253.00 mg/l
LC50 (Vapor)	102.00 mg/l

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Xylene 1330-20-7	3500 mg/kg (Rat)	1100 mg/kg (Rabbit)	6700 ppm (Rat)4 h
Heavy aromatic naptha 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m³(Rat)4 h
ALIPHATIC NAPHTHA 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Zinc oxide 1314-13-2	5000 mg/kg (Rat)	-	-
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h
Naphthalene 91-20-3	1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m³(Rat)1 h

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information No information available

Component Information No information available

Serious eye damage/eye irritation

Product Information No information available **Component Information** • No information available

Respiratory or skin sensitization

Product Information No information available **Component Information** No information available

Germ cell mutagenicity

Product Information No information available **Component Information** • No information available

Carcinogenicity

Product Information

• The table below indicates whether each agency has listed any ingredient as a carcinogen **Component Information**

Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene	-	Group 3	-	
1330-20-7				
Ethylbenzene	-	Group 2B	-	
100-41-4				
Naphthalene	-	Group 2B	Reasonably Anticipated	
91-20-3				

Reproductive toxicity

Product Information

 No information available Component Information

No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Other adverse effects

Product Information
No information available
Component Information
No information available

Aspiration hazard

Product Information

No information available

Component Information

No information available

12. Ecological information

12.1 Toxicity

Ecotoxicity

No information available

1.43299 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Xylene	-	LC50: 96 h Pimephales promelas	EC50: 48 h water flea 3.82 mg/L
1330-20-7		13.4 mg/L flow-through LC50: 96 h	LC50: 48 h Gammarus lacustris 0.6
		Oncorhynchus mykiss 2.661 - 4.093	mg/L
		mg/L static LC50: 96 h	
		Oncorhynchus mykiss 13.5 - 17.3	
		mg/L LC50: 96 h Lepomis	
		macrochirus 13.1 - 16.5 mg/L	
		flow-through LC50: 96 h Lepomis	
		macrochirus 19 mg/L LC50: 96 h	
		Lepomis macrochirus 7.711 - 9.591	
		mg/L static LC50: 96 h Pimephales	
		promelas 23.53 - 29.97 mg/L static	
		LC50: 96 h Cyprinus carpio 780	
		mg/L semi-static LC50: 96 h	
		Cyprinus carpio 780 mg/L LC50: 96	
		h Poecilia reticulata 30.26 - 40.75	
		mg/L static	

Heavy aromatic naptha	-	LC50: 96 h Pimephales promelas	EC50: 48 h Daphnia magna 0.95
64742-94-5		19 mg/L static LC50: 96 h	mg/L
		Oncorhynchus mykiss 2.34 mg/L	
		LC50: 96 h Lepomis macrochirus	
		1740 mg/L static LC50: 96 h	
		Pimephales promelas 45 mg/L	
		flow-through LC50: 96 h	
		Pimephales promelas 41 mg/L	
ALIPHATIC NAPHTHA	EC50: 72 h Pseudokirchneriella	-	-
64742-89-8	subcapitata 4700 mg/L		
Zinc oxide	LC50: 0.136 mg/l	LC50: 0.169 mg/l	-
1314-13-2			
Ethylbenzene	EC50: 72 h Pseudokirchneriella	LC50: 96 h Oncorhynchus mykiss	EC50: 48 h Daphnia magna 1.8 -
100-41-4	subcapitata 4.6 mg/L EC50: 96 h	11.0 - 18.0 mg/L static LC50: 96 h	2.4 mg/L
	Pseudokirchneriella subcapitata 438		
	mg/L EC50: 72 h	semi-static LC50: 96 h Pimephales	
	Pseudokirchneriella subcapitata 2.6		
	- 11.3 mg/L static EC50: 96 h	flow-through LC50: 96 h Lepomis	
	Pseudokirchneriella subcapitata 1.7	macrochirus 32 mg/L static LC50:	
	- 7.6 mg/L static	96 h Pimephales promelas 9.1 -	
		15.6 mg/L static LC50: 96 h Poecilia	
		reticulata 9.6 mg/L static	
Naphthalene	-	LC50: 96 h Pimephales promelas	LC50: 48 h Daphnia magna 2.16
91-20-3		5.74 - 6.44 mg/L flow-through LC50:	mg/L EC50: 48 h Daphnia magna
		96 h Oncorhynchus mykiss 1.6	1.96 mg/L Flow through EC50: 48 h
		mg/L flow-through LC50: 96 h	Daphnia magna 1.09 - 3.4 mg/L
		Oncorhynchus mykiss 0.91 - 2.82	Static
		mg/L static LC50: 96 h Pimephales	
		promelas 1.99 mg/L static LC50: 96	
		h Lepomis macrochirus 31.0265	
		mg/L static	

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Xylene	2.77 - 3.15
1330-20-7	
Heavy aromatic naptha	6.1
64742-94-5	
Ethylbenzene	3.118
100-41-4	
Naphthalene	3.3
91-20-3	

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport Information

Note

This product can be shipped as Limited Quantity per the requirements in 49 CFR 172.315.

	Quantity limitations apply. This product may be reclassified as Consumer Commodity, ORM-D, when shipped by ground; packaging quantity limitations apply.			
DOT	Quarts and gallons ship as limited quantity.			
MEX	no data available			
IMDG Proper shipping name	UN1263, Paint, 3, III			
IATA Proper shipping name	UN1263, Paint, 3, III			

15. Regulatory information

15.1 International Inventories

TSCA DSL EINECS/ELINCS ENCS IECSC	Complies - Complies - Complies
KECL	Complies
PICCS	-
AICS	-
NZIoC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIOC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %	Weight-%
Zinc	1.0	70 - 80
7440-66-6		
Xylene	1.0	5 - 10
1330-20-7		
Zinc oxide	1.0	1 - 5
1314-13-2		
Ethylbenzene	0.1	1 - 5
100-41-4		
Naphthalene	0.1	< 1
Naphthalene 91-20-3		

15.3 Pesticide Information

Not applicable

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65	
Ethylbenzene - 100-41-4	Carcinogen	
Naphthalene - 91-20-3	Carcinogen	
Toluene - 108-88-3	Developmental	
	Female Reproductive	
CUMENE - 98-82-8	Carcinogen	
Lead - 7439-92-1	Carcinogen	
	Developmental	
	Female Reproductive	
	Male Reproductive	
Cadmium - 7440-43-9	Carcinogen	
	Developmental	
	Male Reproductive	
Benzene - 71-43-2	Carcinogen	
	Developmental	
	Male Reproductive	

16. Other information

<u>NFPA</u>	Health Hazard 2	Flammability 3	Instability 0	Physical and chemical
HMIS	Health Hazard 2*	Flammability 3	Physical Hazard 0	hazards - Personal protection X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists) Ceiling (C) DOT (Department of Transportation) EPA (Environmental Protection Agency) IARC (International Agency for Research on Cancer) International Air Transport Association (IATA) International Maritime Dangerous Goods (IMDG) NIOSH (National Institute for Occupational Safety and Health) NTP (National Toxicology Program) OSHA (Occupational Safety and Health Administration of the US Department of Labor) PEL (Permissible Exposure Limit) Reportable Quantity (RQ) Skin designation (S*) STEL (Short Term Exposure Limit) TLV® (Threshold Limit Value) TWA (time-weighted average)

Revision Date Revision Note 20-Nov-2017

No information available Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet