

# Safety Data Sheet

## 1. Identification

Product Information. 1130000

Product Name: Pettit HRT ECO - 1300 Pontoon Gray

Recommended Use. Paints

Uses advised against. Read label instructions and SDS

Supplier. Modern Recreational Technologies, Inc.

2220 Highway 70 SE., Suite 100

Hickory, NC 28602 800-728-8258

Emergency telephone number. Chemtrec: +1-800-424-9300 USA

Chemtrec: +1 703-527-3887 ex-USA

24 hrs./day, 7 days/week

## 2. Hazards Identification

#### GHS Classification in accordance with 29 CFR 1910.1200

Flammable Liquid, category 3
Germ Cell Mutagenicity, category 1B
Carcinogenicity, category 1B
Reproductive Toxicity, category 1B
STOT, repeated exposure, category 1
Acute Toxicity, Oral, category 4
Acute Toxicity, Inhalation, category 3
Serious Eye Damage, category 1

### **GHS Pictograms**









## Signal Word

Danger

### **Unknown Acute Toxicity**

15.9% of the mixture consists of ingredient(s) of unknown acute toxicity

## **HAZARD STATEMENTS**

Flammable liquid and vapor.

Harmful if swallowed.

Causes serious eye damage.

Toxic if inhaled.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

## Precautionary Statements - Prevention.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, sparks, open flames, hot surfaces. No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash face and hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, eye protection, face protection

#### Precautionary Statements - Response.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Immediately call a poison center or doctor.

Immediately call a poison center/doctor.

Rinse mouth.

In case of fire: Use CO<sub>2</sub> dry chemical or foam to extinguish.

#### Precautionary Statements - Storage.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

### Precautionary Statements - Disposal.

Dispose of contents in accordance with local, regional, national, international regulations.

## 3. Composition/Information on Ingredients

<u>Chemical Name</u>	CAS-No.	Wt. %
Solvent naphtha (petroleum), light aromatic	64742-95-6	10-25
Zinc oxide	1314-13-2	10-25
Barium Sulfate	7727-43-7	10-25
1,2,4-TRIMETHYLBENZENE	95-63-6	2.5-10
Titanium Dioxide	13463-67-7	2.5-10
Zinc, bis[1-(hydroxy-kO)-2(1H)-pyridinethionato-kS2]-, (T-4)-	13463-41-7	2.5-10
Tralopyril	122454-29-9	2.5-10
Talc	14807-96-6	2.5-10
MAGNESITE	546-93-0	1.0-2.5
Propanol, oxybis-, dibenzoate	27138-31-4	1.0-2.5
XYLENE	1330-20-7	1.0-2.5
Benzene, (1-methylethyl)-	98-82-8	0.1-1.0
Ethyl Benzene	100-41-4	0.1-1.0

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid Measures

## Description of first-aid measures.

## General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice. Call a poison control center or doctor for treatment advice.

#### Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

#### Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

#### Eye contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

#### Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

#### Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

#### Notes to physician.

Treat symptomatically.

## 5. Fire-fighting Measures

### Extinguishing media.

## Suitable extinguishing media.

Use:. Dry powder. Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

### Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

## Special hazards arising from the substance or mixture.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

#### Advice for firefighters.

Evacuate personnel to safe areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### Accidental Release Measures

### Personal precautions, protective equipment and emergency procedures.

## Personal precautions.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

## Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

#### **Environmental precautions.**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

### Methods and materials for containment and cleaning up.

#### Methods for Containment.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

## Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

## Reference to other sections.

See section 8 for more information.

## 7. Handling and Storage

## Conditions for safe storage, including any incompatibilities.

#### Advice on safe handling.

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Ground and bond containers when transferring material.

## Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exp	posure Limits
-----------------------------------	---------------

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Zinc oxide	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	N.E.
Barium Sulfate	5 mg/m <sup>3</sup>	N.E.	15 mg/m <sup>3</sup>	N.E.
1,2,4-TRIMETHYLBENZENE	10 ppm	N.E.	N.E.	N.E.
Titanium Dioxide	0.2 mg/m <sup>3</sup>	N.E.	15 mg/m <sup>3</sup>	N.E.
Talc	2 mg/m <sup>3</sup>	N.E.	N.E.	N.E.
XYLENE	20 ppm	N.E.	100 ppm	N.E.
Benzene, (1-methylethyl)-	5 ppm	N.E.	50 ppm	N.E.
Ethyl Benzene	20 ppm	N.E.	100 ppm	N.E.

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

#### **Engineering Measures.**

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

## Personal protective equipment.

#### Eye/Face Protection.

If splashes are likely to occur, wear:. Face-shield. Safety glasses with side-shields. Tightly fitting safety goggles.

## Skin and body protection.

Use:. Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

## Respiratory protection.

In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

## 9. Physical and chemical properties.

## Information on basic physical and chemical properties.

Physical state Liquid

Appearance No Information

**Color** Gray

Odor Aromatic solvent
Odor Threshold No Information
pH No Information
Melting/freezing point., °C (°F) No Information
Flash Point., °C (°F) 44 (111.20)

Boiling point/boiling range., °C (°F)

138 - 3,600 (280.4 - 6512)

Evaporation rate

No Information Available

Explosive properties.No InformationVapor pressure.No InformationVapor density.No Information

Specific Gravity. (g/cm<sup>3</sup>) 1.459

Water solubility.No InformationPartition coefficient.No InformationAutoignition temperature.,°CNo InformationDecomposition Temperature °C.No InformationViscosity, kinematic.> 22mm2/sec

Other information.

Volatile organic compounds (VOC) content.

No Information
12.150

## 10. Stability and Reactivity

### Reactivity.

Stable under normal conditions.

#### Chemical stability.

Stable under recommended storage conditions.

#### Possibility of hazardous reactions.

None known based on information supplied.

## Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

### Incompatible Materials.

None known based on information supplied.

## Hazardous Decomposition Products.

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

## 11. Toxicological Information

## Information on toxicological effects.

Acute toxicity.

**Product Information** 

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 624.4 mg/kg
ATEmix (dermal) 14,780.6 mg/kg
ATEmix (inhalation - dust/mist) 0.84 mg/l

Component Information.

CAS-No.	Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
64742-95-6	Solvent naphtha (petroleum), light aromatic	8400 mg/kg Rat	N.I.	N.I.
1314-13-2	Zinc oxide	>5000 mg/kg Rat	N.I.	>5.7 mg/L Rat (Dust)
95-63-6	1,2,4-TRIMETHYLBENZENE	3280 mg/kg Rat	>3160 mg/kg Rabbit	18 mg/L Rat (Vapor)
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	N.I.	5.09 mg/L Rat (Dust)
13463-41-7	Zinc, bis[1-(hydroxy-kO)-2(1H)- pyridinethionato-kS2]-, (T-4)-	177 mg/kg Rat	>2000 mg/kg Rat	N.I.
122454-29-9	Tralopyril	27 mg/kg Rat	N.I.	N.I.
27138-31-4	Propanol, oxybis-, dibenzoate	3914 mg/kg Rat	>2000 mg/kg Rat	N.I.
1330-20-7	XYLENE	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat (Vapor)
98-82-8	Benzene, (1-methylethyl)-	1400 mg/kg Rat	1474 mg/kg Rabbit	>3577 ppm Rat (Gas/Mist)
100-41-4	Ethyl Benzene	3500 mg/kg Rat	15400 mg/kg Rabbit	NA (Dust)

N.I. = No Information

#### Skin corrosion/irritation.

SKIN IRRITANT.

## Eye damage/irritation.

No Information

## Respiratory or skin sensitization.

No Information

## Ingestion.

May be harmful if swallowed.

## Germ cell mutagenicity.

No Information

### Carcinogenicity.

No Information

CAS-No.	Chemical Name	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
13463-67-7	Titanium Dioxide	IARC Group 2B	-	-
14807-96-6	Talc	IARC Group 3	-	-
1330-20-7	XYLENE	IARC Group 3	-	-
98-82-8	Benzene, (1-methylethyl)-	IARC Group 2B	NTP Reasonally Anticipated to be Human Carcinogen	-
100-41-4	Ethyl Benzene	IARC Group 2B	-	-

## Reproductive toxicity.

No Information

## Specific target organ systemic toxicity (single exposure).

No Information

## Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

## Aspiration hazard.

No Information

## Primary Route(s) of Entry

No Information

## 12. Ecological Information

## Toxicity.

27.24% of the mixture consists of ingredient(s) of unknown aquatic toxicity

## **Ecotoxicity effects.**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Solvent naphtha (petroleum), light aromatic 64742-95-6	-	LC50 96 h Oncorhynchus mykiss 9.22 mg/L	EC50 48 h Daphnia magna 6.14 mg/L
Zinc oxide 1314-13-2	-	LC50 96 h Danio rerio 1.55 mg/L	-
1,2,4-TRIMETHYLBENZENE 95-63-6	-	LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L	EC50 48 h Daphnia magna 6.14 mg/L
Talc 14807-96-6	-	LC50 96 h Brachydanio rerio >100 g/L	-
Propanol, oxybis-, dibenzoate 27138-31-4	-	LC50 96 h Pimephales promelas 3.7 mg/L	-
XYLENE 1330-20-7	-	LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40.	EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L
Benzene, (1-methylethyl)- 98-82-8	EC50 72 h Pseudokirchneriella subcapitata 2.6 mg/L	LC50 96 h Pimephales promelas 6.04 - 6.61 mg/L, LC50 96 h Oncorhynchus mykiss 4.8 mg/L, LC50 96 h Oncorhynchus mykiss 2.7 mg/L, LC50 96 h Poecilia reticulata 5.1 mg/L	EC50 48 h Daphnia magna 0.6 mg/L, EC50 48 h Daphnia magna 7.9 - 14.1 mg/L
Ethyl Benzene 100-41-4	EC50 72 h Pseudokirchneriella subcapitata 4.6 mg/L, EC50 96 h Pseudokirchneriella subcapitata >438 mg/L, EC50 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L, EC50 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L	LC50 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L, LC50 96 h Oncorhynchus mykiss 4.2 mg/L, LC50 96 h Pimephales promelas 7.55 - 11 mg/L, LC50 96 h Lepomis macrochirus 32 mg/L, LC50 96 h Pimephales promelas 9.1 - 15.6 mg/L, LC50 96 h Poecilia reticulata 9.6 mg/L	

## Persistence and degradability.

No data are available on the product itself.

## Bioaccumulative potential.

Discharge into the environment must be avoided.

CAS-No.	Chemical Name	log POW
95-63-6	1,2,4-TRIMETHYLBENZENE	3.63
13463-41-7	Zinc, bis[1-(hydroxy-kO)-2(1H)-pyridinethionato kS2]-, (T-4)-	0.9
1330-20-7	XYLENE	2.77 - 3.15
98-82-8	Benzene, (1-methylethyl)-	3.55
100-41-4	Ethyl Benzene	3.6

## Mobility in soil.

No information

### Other adverse effects.

No information

## 13. Disposal Considerations

### Waste Disposal Guidance.

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes can not be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## Transport Information

## DOT

Shipping Name: UN1263 Hazard Class: 3 UN/NA Number: 1263 Packing Group: III

Additional Information: LTD QTY EXCEPTION: This product may be reclassified as "limited quantity" per 49 CFR 173.150

(b)(3) and thus is exempt from labeling requirements when transported within the U.S. by motor vehicle or rail only. This exception applies as long as it is packaged with strong outer packaging and

with inner packagings not over 5.0 L (1.3 gallons) net capacity each.

## **IMDG**

Proper Shipping Name: Paint Hazard Class: 3
UN Number: 1263
Packing Group: III

#### **IATA**

**TCSI** 

Proper Shipping Name: UN1263, Paint

Hazard Class: 3
Packing Group: III

## 15. Regulatory Information

# International Inventories:

TSCA Complies

DSL DSL/NDSL EINECS/ELINCS ENCS IECSC KECI PICCS AIIC NZIOC -

**TSCA** United States Toxic Substances Control Act Section 8(b) Inventory.

DSL Canadian Domestic Substances List

DSL/NDSL Canadian Domestic Substances List/Canadian Non-Domestic Substances List

EINECS/ELINCS European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.

ENCS Japan Existing and New Chemical Substances.

IECSC China Inventory of Existing Chemical Substances.

KECL Korean Existing and Evaluated Chemical Substances.

PICCS Philippines Inventory of Chemicals and Chemical Substances.

AllC Australian Inventory of Chemical Substances.

NZIOC New Zealand Inventory of Chemicals.

TCSI Taiwan Chemical Substance Inventory

## **U.S. Federal Regulations:**

### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

<u>Chemical Name</u>	<u>CAS-No.</u>	Weight Percent
1,2,4-TRIMETHYLBENZENE	95-63-6	2.5-10
XYLENE	1330-20-7	1.0-2.5
Benzene, (1-methylethyl)-	98-82-8	0.1-1.0
Ethyl Benzene	100-41-4	0.1-1.0

#### **TOXIC SUBSTANCES CONTROL ACT 12(b):**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:.

Chemical NameCAS-No.Lead7439-92-1

## U.S. EPA PESTICIDE INFORMATION

EPA Pesticide Registration Number: 60061-148

**EPA STATEMENT:** This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

EPA PESTICIDE LABEL: WARNING. Combustible liquid and vapor. Vapor harmful. Harmful or fatal if

swallowed. Causes substantial but temporary eye injury. Causes skin irritation.

### **ADDITIONAL INFORMATION**

Additional Information - Sxn 15: No Information

## **CALIFORNIA PROPOSITION 65 CARCINOGENS**



## WARNING

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
Titanium Dioxide	13463-67-7
Benzene, (1-methylethyl)-	98-82-8
Ethyl Benzene	100-41-4
Carbon black	1333-86-4
Crystalline silica (Quartz) (Respirable)	14808-60-7
Lead	7439-92-1

## **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**



## **WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u> CAS-No.

Lead 7439-92-1

### NOTICE

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

## 16. Other Information

Revision Date: 4/26/2023 Supersedes Date: 11/23/2022

Reason for revision: Revision Description Changed

Product Composition Changed Substance CAS Number Changed

Substance and/or Product Properties Changed in Section(s):

09 - Physical & Chemical Information

11 - Toxicological Information

16 - Other Information

Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health:	3*	Flammability:	3	Physical Hazard:	0	Personal Protection:	Н
NFPA Ratir	nas:						
Health:	.g	Flammability:	3	Instability:	n	Physical & Chemical:	

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.