



## Safety Data Sheet

### 1. Identification

<b>Product Information.</b>	1300520
<b>Product Name:</b>	EZ-Fabriccoat Aerosol Gray
<b>Recommended Use.</b>	Paints
<b>Uses advised against.</b>	Read label instructions and SDS
<b>Supplier.</b>	Kop-Coat, Inc. / Pettit Marine Paint Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466
<b>Emergency telephone number.</b>	Chemtrec: +1-800-424-9300 USA Chemtrec: +1 703-527-3887 ex-USA 24 hrs./day, 7 days/week

### 2. Hazards Identification

#### GHS Classification in accordance with 29 CFR 1910.1200

Acute Toxicity, Inhalation, category 4  
Carcinogenicity, category 1B  
Eye Irritation, category 2A  
Germ Cell Mutagenicity, category 1B  
Reproductive Toxicity, category 2  
STOT, single exposure, category 3, NE

#### GHS Pictograms



#### Signal Word

Danger

#### Unknown Acute Toxicity

42.6% of the mixture consists of ingredient(s) of unknown acute toxicity

#### HAZARD STATEMENTS

Extremely flammable aerosol.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause drowsiness or dizziness.  
May cause genetic defects.  
May cause cancer.  
Suspected of damaging fertility or the unborn child.

#### Precautionary Statements - Prevention.

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Wash face and hands and any exposed skin thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response.**

If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.

**Precautionary Statements - Storage.**

Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.  
 Store at temperatures not exceeding 50 °C/122 °F. Protect from sunlight.

**Precautionary Statements - Disposal.**

Dispose of contents in accordance with local/regional/national/international regulations.

### 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>
ACETONE	67-64-1	25-50
Butanone	78-93-3	10-25
Propane	74-98-6	10-25
Methyl isobutyl ketone	108-10-1	10-25
Butane	106-97-8	2.5-10
XYLENE	1330-20-7	1.0-2.5
GLYCOL ETHER PNB	5131-66-8	1.0-2.5
Titanium dioxide	13463-67-7	1.0-2.5
Amorphous Silica	7631-86-9	0.1-1.0
Toluene	108-88-3	0.1-1.0
Solvent naphtha (petroleum), light aromatic	64742-95-6	0.1-1.0
Ethyl Benzene	100-41-4	0.1-1.0

The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid Measures

**Description of first-aid measures.****General advice.**

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice.  
 Call a poison control center or doctor for treatment advice.

**Inhalation.**

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

**Skin contact.**

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

**Eye contact.**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

**Ingestion.**

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

**Symptoms.**

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

**Notes to physician.**

Treat symptomatically.

**5. Fire-fighting Measures****Extinguishing media.****Suitable extinguishing media.**

Use: Dry powder. Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Extinguishing media which shall not be used for safety reasons.**

Water may be unsuitable for extinguishing fires.

**Special hazards arising from the substance or mixture.**

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

**Advice for firefighters.**

Evacuate personnel to safe areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. Accidental Release Measures****Personal precautions, protective equipment and emergency procedures.****Personal precautions.**

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

**Advice for emergency responders.**

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

**Environmental precautions.**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

**Methods and materials for containment and cleaning up.****Methods for Containment.**

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

**Methods for cleaning up.**

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

**Reference to other sections.**

See section 8 for more information.

## 7. Handling and Storage

### Conditions for safe storage, including any incompatibilities.

#### **Advice on safe handling.**

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not puncture or incinerate cans. Use according to package label instructions. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. Ground and bond containers when transferring material. All equipment used when handling the product must be grounded.

#### **Hygiene measures.**

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### **Storage Conditions.**

Keep container closed when not in use. Do not puncture or incinerate cans. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedings. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
ACETONE	250 ppm	500 ppm	1000 ppm	N.E.
Butanone	200 ppm	300 ppm	200 ppm	N.E.
Propane	N.E.	N.E.	1000 ppm	N.E.
Methyl isobutyl ketone	20 ppm	75 ppm	100 ppm	N.E.
Butane	N.E.	1000 ppm	N.E.	N.E.
XYLENE	100 ppm	150 ppm	100 ppm	N.E.
Titanium dioxide	10 mg/m <sup>3</sup>	N.E.	15 mg/m <sup>3</sup>	N.E.
Toluene	20 ppm	N.E.	200 ppm	300 ppm
Ethyl Benzene	20 ppm	N.E.	100 ppm	N.E.

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

#### **Engineering Measures.**

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

#### **Personal protective equipment.**

##### **Eye/Face Protection.**

If splashes are likely to occur, wear: Face-shield. Safety glasses with side-shields. Tightly fitting safety goggles.

##### **Skin and body protection.**

Use: Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

##### **Respiratory protection.**

Do not inhale aerosol. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

## 9. Physical and chemical properties.

### Information on basic physical and chemical properties.

Physical state	Aerosol
Appearance	No Information
Color	Gray
Odor	No Information
Odor Threshold	No Information
pH	No Information
Melting/freezing point., °C (°F)	No Information
Flash Point., °C (°F)	-20 (-4.00)
Boiling point/boiling range., °C (°F)	56 - 3,000 (132.8 - 5432)
Evaporation rate	No Information
Explosive properties.	No Information
Vapor pressure.	No Information
Vapor density.	No Information
Specific Gravity. (g/cm <sup>3</sup> )	0.758
Water solubility.	No Information
Partition coefficient.	No Information
Autoignition temperature., °C	No Information
Decomposition Temperature °C.	No Information
Viscosity, kinematic.	No Information
<b>Other information.</b>	
Volatile organic compounds (VOC) content.	622 g/L
Density, lb/gal	6.311

## 10. Stability and Reactivity

### Reactivity.

Stable under normal conditions.

### Chemical stability.

Stable under recommended storage conditions.

### Possibility of hazardous reactions.

None known based on information supplied.

### Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

### Incompatible Materials.

None known based on information supplied.

### Hazardous Decomposition Products.

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

## 11. Toxicological Information

### Information on toxicological effects.

Acute toxicity.

#### Product Information

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	5,763.9 mg/kg
ATEmix (dermal)	3,055.0 mg/kg
ATEmix (inhalation - dust/mist)	2.94 mg/l

#### Component Information.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>LD50 Oral</u>	<u>LD50 Dermal</u>	<u>LC50 Inhalation</u>
67-64-1	ACETONE	6006 mg/kg Rat	2002 mg/kg Rat	50.1 mg/L Rat (Vapor)
78-93-3	Butanone	2483 mg/kg Rat	5000 mg/kg Rabbit	11700 ppm Rat (Gas/Mist)
74-98-6	Propane	N.I.	N.I.	>800000 ppm Rat (Gas/Mist)
108-10-1	Methyl isobutyl ketone	2080	3000	> 2000 ppm ( Rat ) 4 h (Vapor)
106-97-8	Butane	N.I.	N.I.	658 mg/L Rat (Vapor)
1330-20-7	XYLENE	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat (Vapor)
5131-66-8	GLYCOL ETHER PNB	1900 mg/kg Rat	>2000 mg/kg Rat	N.I.
7631-86-9	Amorphous Silica	7900 mg/kg Rat	>5000 mg/kg Rabbit	N.I.
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat (Vapor)
64742-95-6	Solvent naphtha (petroleum), light aromatic	8400 mg/kg Rat	N.I.	N.I.
100-41-4	Ethyl Benzene	3500 mg/kg Rat	15400 mg/kg Rabbit	NA (Dust)

N.I. = No Information

### Skin corrosion/irritation.

SKIN IRRITANT.

### Eye damage/irritation.

No Information

### Respiratory or skin sensitization.

No Information

### Ingestion.

May be harmful if swallowed.

### Germ cell mutagenicity.

No Information

### Carcinogenicity.

No Information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
108-10-1	Methyl isobutyl ketone	IARC Group 2B	-	-
1330-20-7	XYLENE	IARC Group 3	-	-
13463-67-7	Titanium dioxide	IARC Group 2B	-	-
7631-86-9	Amorphous Silica	IARC Group 3	-	-
108-88-3	Toluene	IARC Group 3	-	-
100-41-4	Ethyl Benzene	IARC Group 2B	-	-

### Reproductive toxicity.

No Information

### Specific target organ systemic toxicity (single exposure).

No Information

### Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard.

No Information

**Primary Route(s) of Entry**

Inhalation

**12. Ecological Information****Toxicity.**

22.37% of the mixture consists of ingredient(s) of unknown aquatic toxicity

**Ecotoxicity effects.**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	-	LC50 96 h <i>Oncorhynchus mykiss</i> 4.74 - 6.33 mg/L, LC50 96 h <i>Pimephales promelas</i> 6210 - 8120 mg/L, LC50 96 h <i>Lepomis macrochirus</i> 8300 mg/L	EC50 48 h <i>Daphnia magna</i> 10294 - 17704 mg/L, EC50 48 h <i>Daphnia magna</i> 12600 - 12700 mg/L
Butanone 78-93-3	-	LC50 96 h <i>Pimephales promelas</i> 3130 - 3320 mg/L	EC50 48 h <i>Daphnia magna</i> >520 mg/L, EC50 48 h <i>Daphnia magna</i> 5091 mg/L, EC50 48 h <i>Daphnia magna</i> 4025 - 6440 mg/L
Methyl isobutyl ketone 108-10-1	EC50 96 h <i>Pseudokirchneriella subcapitata</i> 400 mg/L	LC50 96 h <i>Pimephales promelas</i> 496 - 514 mg/L	EC50 48 h <i>Daphnia magna</i> 170 mg/L
XYLENE 1330-20-7	-	LC50 96 h <i>Pimephales promelas</i> 13.4 mg/L, LC50 96 h <i>Oncorhynchus mykiss</i> 2.661 - 4.093 mg/L, LC50 96 h <i>Oncorhynchus mykiss</i> 13.5 - 17.3 mg/L, LC50 96 h <i>Lepomis macrochirus</i> 13.1 - 16.5 mg/L, LC50 96 h <i>Lepomis macrochirus</i> 19 mg/L, LC50 96 h <i>Lepomis macrochirus</i> 7.711 - 9.591 mg/L, LC50 96 h <i>Pimephales promelas</i> 23.53 - 29.97 mg/L, LC50 96 h <i>Cyprinus carpio</i> 780 mg/L, LC50 96 h <i>Cyprinus carpio</i> >780 mg/L, LC50 96 h <i>Poecilia reticulata</i> 30.26 - 40.	EC50 48 h water flea 3.82 mg/L, LC50 48 h <i>Gammarus lacustris</i> 0.6 mg/L
Amorphous Silica 7631-86-9	EC50 72 h <i>Pseudokirchneriella subcapitata</i> 440 mg/L	LC50 96 h <i>Brachydanio rerio</i> 5000 mg/L	EC50 48 h <i>Ceriodaphnia dubia</i> 7600 mg/L
Toluene 108-88-3	EC50 96 h <i>Pseudokirchneriella subcapitata</i> >433 mg/L, EC50 72 h <i>Pseudokirchneriella subcapitata</i> 12.5 mg/L	LC50 96 h <i>Pimephales promelas</i> 15.22 - 19.05 mg/L, LC50 96 h <i>Pimephales promelas</i> 12.6 mg/L, LC50 96 h <i>Oncorhynchus mykiss</i> 5.89 - 7.81 mg/L, LC50 96 h <i>Oncorhynchus mykiss</i> 14.1 - 17.16 mg/L, LC50 96 h <i>Oncorhynchus mykiss</i> 5.8 mg/L, LC50 96 h <i>Lepomis macrochirus</i> 11.0 - 15.0 mg/L, LC50 96 h <i>Oryzias latipes</i> 54 mg/L, LC50 96 h <i>Poecilia reticulata</i> 28.2 mg/L, LC50 96 h <i>Poecilia reticulata</i> 50.87 - 70.34 mg/L	EC50 48 h <i>Daphnia magna</i> 5.46 - 9.83 mg/L, EC50 48 h <i>Daphnia magna</i> 11.5 mg/L
Solvent naphtha (petroleum), light aromatic 64742-95-6	-	LC50 96 h <i>Oncorhynchus mykiss</i> 9.22 mg/L	EC50 48 h <i>Daphnia magna</i> 6.14 mg/L
Ethyl Benzene 100-41-4	EC50 72 h <i>Pseudokirchneriella subcapitata</i> 4.6 mg/L, EC50 96 h <i>Pseudokirchneriella subcapitata</i> >438 mg/L, EC50 72 h <i>Pseudokirchneriella subcapitata</i> 2.6 - 11.3 mg/L, EC50 96 h <i>Pseudokirchneriella subcapitata</i> 1.7 - 7.6 mg/L	LC50 96 h <i>Oncorhynchus mykiss</i> 11.0 - 18.0 mg/L, LC50 96 h <i>Oncorhynchus mykiss</i> 4.2 mg/L, LC50 96 h <i>Pimephales promelas</i> 7.55 - 11 mg/L, LC50 96 h <i>Lepomis macrochirus</i> 32 mg/L, LC50 96 h <i>Pimephales promelas</i> 9.1 - 15.6 mg/L, LC50 96 h <i>Poecilia reticulata</i> 9.6 mg/L	EC50 48 h <i>Daphnia magna</i> 1.8 - 2.4 mg/L

**Persistence and degradability.**

No data are available on the product itself.

**Bioaccumulative potential.**

Discharge into the environment must be avoided.

<b><u>CAS-No.</u></b>	<b><u>Chemical Name</u></b>	<b><u>log POW</u></b>
67-64-1	ACETONE	-0.24
78-93-3	Butanone	0.3
74-98-6	Propane	2.3
108-10-1	Methyl isobutyl ketone	1.19
106-97-8	Butane	2.89
1330-20-7	XYLENE	2.77 - 3.15
108-88-3	Toluene	2.7
100-41-4	Ethyl Benzene	3.2

**Mobility in soil.**

No information

**Other adverse effects.**

No information

## 13. Disposal Considerations

**Waste Disposal Guidance.**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

**DOT**

**Shipping Name:** Aerosol  
**Hazard Class:** 2.1  
**UN/NA Number:** 1950  
**Packing Group:** II  
**Additional Information:** LTD QTY: This product may be reclassified as "limited quantity" per 49 CFR 173.150 (b)(2) and 49 CFR 172 Special Provision 149.

**IMDG**

**Proper Shipping Name:** Aerosol  
**Hazard Class:** 2.1  
**UN Number:** 1950  
**Packing Group:** II

**IATA**

**Proper Shipping Name:** UN1950, Aerosol  
**Hazard Class:** 2.1  
**Packing Group:** II

## 15. Regulatory Information

**International Inventories:**



TSCA	Complies
DSL	-
DSL/NDL	-
EINECS/ELINCS	-
ENCS	-
IECSC	-
KECI	-
PICCS	-
AICS	-
NZIoC	-

**TCSI**

TSCA	United States Toxic Substances Control Act Section 8(b) Inventory.
DSL	Canadian Domestic Substances List.
DSL/NDL	Canadian Domestic Substances List/Canadian Non-Domestic Substances List
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
ENCS	Japan Existing and New Chemical Substances.
IECSC	China Inventory of Existing Chemical Substances.
KECL	Korean Existing and Evaluated Chemical Substances.
PICCS	Philippines Inventory of Chemicals and Chemical Substances.
AICS	Australian Inventory of Chemical Substances.
NZIoC	New Zealand Inventory of Chemicals.
TCSI	Taiwan Chemical Substance Inventory

**U.S. Federal Regulations:****SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Weight Percent</u>
Methyl isobutyl ketone	108-10-1	10-25
XYLENE	1330-20-7	1.0-2.5
Ethyl Benzene	100-41-4	0.1-1.0

**TOXIC SUBSTANCES CONTROL ACT 12(b):**

This product does not contain any chemicals that are subject to the reporting requirements of TSCA 12(b).

**CALIFORNIA PROPOSITION 65 CARCINOGENS****WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:.

<u>Chemical Name</u>	<u>CAS-No.</u>
Methyl isobutyl ketone	108-10-1
Titanium dioxide	13463-67-7
Ethyl Benzene	100-41-4
Carbon black	1333-86-4
Benzene, (1-methylethyl)-	98-82-8

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS****WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
Methyl isobutyl ketone	108-10-1
Toluene	108-88-3

**16. Other Information**

**Revision Date:** 8/24/2021 **Supersedes Date:** 9/2/2020

**Reason for revision:** Product Composition Changed  
 Substance and/or Product Properties Changed in Section(s):  
 02 - Hazards Identification  
 03 - Composition/Information on Ingredients  
 09 - Physical & Chemical Information  
 11 - Toxicological Information  
 14 - Transportation Information  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

<b>Health:</b>	2*	<b>Flammability:</b>	4	<b>Physical Hazard:</b>	0	<b>Personal Protection:</b>	X
----------------	----	----------------------	---	-------------------------	---	-----------------------------	---

**NFPA Ratings:**

<b>Health:</b>	2	<b>Flammability:</b>	4	<b>Instability:</b>	0	<b>Physical &amp; Chemical:</b>	---
----------------	---	----------------------	---	---------------------	---	---------------------------------	-----

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.