

Safety Data Sheet
REGULATORY REACH 1907/2006
1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE



Safety Data Sheet dated 4/4/2023, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name : IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

Trade code : 1750008

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product type and use: Painting product for car refinish and industrial job-professional use-

1.3. Details of the supplier of the safety data sheet

Supplier: Modern Recreational Technologies, Inc.
2220 Highway 70 SE., Suite 100 Hickory, NC 28602
800-728-8258

Competent person responsible for the safety data sheet:

1.4. Emergency telephone number

Chemtrec: +1-800-424-9300 USA






Chemtrec: +1 703-527-3887 ex-USA

24 hrs./day, 7 days/week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

-  Warning, Flam. Liq. 3, Flammable liquid and vapour.
-  Danger, Skin Corr. 1C, Causes severe skin burns and eye damage.
-  Danger, Eye Dam. 1, Causes serious eye damage.
-  Warning, Skin Sens. 1, May cause an allergic skin reaction.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

DECL10: This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of Regulation (EC) 1272/2008.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

Danger

Hazard statements:

- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P210 Keep away from heat - No smoking.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor/...
- P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

- n-butyl acetate
- Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified
- 1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine

Special provisions according to Annex XVII of REACH and subsequent amendments:

- Restricted to professional users.

2.3. Other hazards

- No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

- No other hazards




SECTION 3: Composition/information on ingredients

3.1. Substances

- N.A.

3.2. Mixtures

- Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 12,5\%$ $< 15\%$	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-21194854 93-29	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H336
$\geq 12,5\%$ $< 15\%$	titanium dioxide; [in powder form containing 1 % or more of particles with	Index number: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5	 3.6/2 Carc. 2 H351

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

	aerodynamic diameter ≤ 10 µm]		
>=10% -< 12,5%	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	Index number: 649-356-00-4 CAS: 64742-95-6 EC: 265-199-0 REACH No.: 01-21194558 51-35	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H335 3.8/3 STOT SE 3 H336 3.10/1 Asp. Tox. 1 H304 4.1/C2 Aquatic Chronic 2 H411 DECLP (CLP)*
>=5% -< 7%	xylene	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-21194882 16-32	2.6/3 Flam. Liq. 3 H226 4.1/C3 Aquatic Chronic 3 H412 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332 3.2/2 Skin Irrit. 2 H315 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H335 3.10/1 Asp. Tox. 1 H304 3.9/2 STOT RE 2 H373
>=5% -< 7%	1,3,3-trimethyl-N-(2-me thylpropylidene)-5-[(2- methylpropylidene)ami no]cyclohexanemethyl amine	CAS: 54914-37-3 EC: 259-393-4 REACH No.: 01-21199782 83-28	3.2/1C Skin Corr. 1C H314 3.3/2 Eye Irrit. 2 H319 3.4.2/1 Skin Sens. 1 H317
>=0,1% -< 0,25%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-21194893 70-35	2.6/2 Flam. Liq. 2 H225 4.1/C3 Aquatic Chronic 3 H412 3.1/4/Inhal Acute Tox. 4 H332 3.10/1 Asp. Tox. 1 H304 3.9/2 STOT RE 2 H373
559 ppm	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC: 919-857-5 REACH No.: 01-21194632 58-33	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336 3.10/1 Asp. Tox. 1 H304
429 ppm	ACRILATO DI N-BUTILE	CAS: 141-32-2 EC: 205-480-7 REACH No.: 01-21194531 55-43	4.1/C3 Aquatic Chronic 3 H412 2.6/3 Flam. Liq. 3 H226 3.1/4/Inhal Acute Tox. 4 H332 3.2/2 Skin Irrit. 2 H315 3.3/2 Eye Irrit. 2 H319 3.4.2/1 Skin Sens. 1 H317 3.8/3 STOT SE 3 H335
189 ppm	2-methoxy-1-methyleth yl acetate	Index number: 607-195-00-7 CAS: 108-65-6	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

		EC: 203-603-9 REACH No.: 01-21194757 91-29	
--	--	--	--

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

CONSULT A PHYSICIAN IMMEDIATELY.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Store between 5 and 35°C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
n-butyl acetate - CAS: 123-86-4
ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7
ACGIH - TWA(8h): 0.2 mg/m³ - Notes: Nanoscale particles; (R); A3 - LRT irr, pneumoconiosis
ACGIH - TWA(8h): 2.5 mg/m³ - Notes: Finescale particles; (R); A3 - LRT irr, pneumoconiosis
xylene - CAS: 1330-20-7

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

National - TWA: 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: pelle
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

ethylbenzene - CAS: 100-41-4
EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
TLV-TWA - 116 mg/m³, 20 ppm

ACRILATO DI N-BUTILE - CAS: 141-32-2
EU - TWA(8h): 11 mg/m³, 2 ppm - STEL: 53 mg/m³, 10 ppm
ACGIH - TWA(8h): 2 ppm - Notes: DSEN, A4 - Irr

2-methoxy-1-methylethyl acetate - CAS: 108-65-6
EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: Skin

DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4
Worker Professional: 960 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Professional: 960 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 480 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Professional: 480 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, local effects
Worker Professional: 859.7 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Professional: 859.7 mg/kg - Exposure: Human Inhalation - Frequency: Short Term (acute)

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified - CAS: 64742-95-6
Worker Professional: 25 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 150 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 32 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

xylene - CAS: 1330-20-7
Worker Professional: 3182 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 442 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Professional: 221 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Professional: 221 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, local effects

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Worker Professional: 300 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Worker Professional: 1500 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

Worker Professional: 208 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 871 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: 08 - Value: 0.36 mg/l

Target: 09 - Value: 35.6 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Marine water sediments - Value: 0.0981 mg/kg

Target: Soil (agricultural) - Value: 0.0903 mg/kg

xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Marine water sediments - Value: 12.46 mg/l

Target: Freshwater sediments - Value: 12.46 mg/l

Target: 09 - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

Target: 08 - Value: 0.327 mg/l

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment. es. CEN/FFP-2 o CEN/FFP-3

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	Grey	--	--
Odour:	CHARACTERISTIC	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	> 35 gradi C.	--	--
Flammability:	Flam. Liq. 3,	--	--

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

	H226		
Lower and upper explosion limit:	N.A.	--	--
Flash point:	>= 23	--	--
Auto-ignition temperature:	400 gradi C.	--	--
Decomposition temperature:	N.A.	--	--
pH:	Not Relevant	--	--
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)	--	--
Solubility in water:	Insolubile	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.D.	--	--
Density and/or relative density:	1.65 Kg/L	--	--
Relative vapour density:	>Air	--	--

Particle characteristics:

Particle size:	N.A.	--	--
----------------	------	----	----

9.2. Other information

Properties	Value	Method:	Notes:
Explosive properties:	2/11 % Volume	--	--
Oxidizing properties:	N.D.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.)

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10000 mg/kg

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

Test: LC50 - Route: Inhalation - Species: Rat > 21.1 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified - CAS: 64742-95-6

a) acute toxicity:

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 6193 mg/m³ - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

Test: LD50 - Route: Oral - Species: Rat 3492 mg/kg

b) skin corrosion/irritation:

Test: Eye Irritant - Species: Rabbit 100 ul/kg

Test: Skin Irritant - Route: Skin - Species: Rabbit

xylene - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 5000 Ppm - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 1700 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 3500 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 4951 mg/m³ - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 2000 Ppm - Duration: 2H

n-butyl acetate - CAS: 123-86-4

OBSERVATIONS ON HUMAN SUBJECTS:

Inhalation: 3300 ppm (16 mg/l), for short periods, cause serious irritation to the eyes and to the nose.

Inhalation: 200-300 ppm (1-1.4 mg/l), for short periods, cause moderate irritation to the eyes and to the nose.

Inhaling the vapours can irritate the respiratory system.

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2,000 ppm for 60 min.

TCLo: 200 ppm

xylene - CAS: 1330-20-7

OBSERVATIONS ON HUMAN SUBJECTS NON-PROFESSIONAL EXPOSURED-

Effects following acute exposure:

Symptoms of intense exposure are: dermatitis, eczema, irritation to the eyes and to the respiratory tract.

Inhaling the vapours can cause dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

PROFESSIONAL EXPOSURED- Effects following acute exposure:

Narcotic at high concentrations.

Irritation through inhalation at 200 ppm (TCLo). Inhalation of 200 ppm has irritating effects in human subjects.

Human subject (oral)(LDLo): 50 mg/kg.

Inhalatory human subject (LCLo) 10000 ppm/6h.

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt sound working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

e) Plant toxicity:

Endpoint: EC50 - Species: Algae = 675 mg/l - Duration h: 72

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified - CAS: 64742-95-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 3.2 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 9.2 mg/l - Duration h: 96

xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 21 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 29 mg/l - Duration h: 96

Endpoint: EC50 - Species: Fish = 35 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 165 mg/l - Duration h: 24

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

12.7. Other adverse effects
None

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



14.1. UN number or ID number
ADR-UN Number: 3469
IATA-UN Number: 3469
IMDG-UN Number: 3469

14.2. UN proper shipping name
ADR-Shipping Name: PAINT, FLAMMABLE, CORROSIVE
IATA-Shipping Name: PAINT, FLAMMABLE, CORROSIVE
IMDG-Shipping Name: PAINT, FLAMMABLE, CORROSIVE

14.3. Transport hazard class(es)
ADR-Class: 3
ADR - Hazard identification number: 38
IATA-Class: 3
IATA-Label: 3 + 8
IMDG-Class: 3

14.4. Packing group
ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

14.5. Environmental hazards
ADR-Environmental Pollutant: NO
IMDG-Marine pollutant: NO
IMDG-EmS: F-E,
S-C

14.6. Special precautions for user
ADR-Subsidiary hazards: 8
ADR-S.P.: 163 367
ADR-Transport category (Tunnel restriction code): 3 (D/E)
IATA-Passenger Aircraft: 354
IATA-Subsidiary hazards: 8
IATA-Cargo Aircraft: 365
IATA-S.P.: A3 A72 A192 A803
IATA-ERG: 3C
IMDG-Subsidiary hazards: 8
IMDG-Stowage and handling: Category A SW2
IMDG-Segregation: -

14.7. Maritime transport in bulk according to IMO instruments

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 28

Restriction 29

Restriction 75

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer if inhaled.
H335 May cause respiratory irritation.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H225 Highly flammable liquid and vapour.
H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1C	3.2/1C	Skin corrosion, Category 1C
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Corr. 1C, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Safety Data Sheet

REGULATORY REACH 1907/2006

1750008 IKONIKOLOR PRO 750 EXPRESS PRIMER GREY BASE

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances (1983)

I.N.R.S. - Fiche Toxicologique

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.